

EonStor[®] Fibre-to-SATA Series RAID Subsystem

High Performance 4G SAN Connectivity
High-density SATA Storage with Enterprise-class Reliability



HIGHLIGHTS

- Single or dual-active RAID controller configurations
- Fault-tolerant enclosure design
- Infortrend's fifth-generation ASIC400 RAID engine
- Two (2) 4G FC host channels per controller
- Four (4) host ports per controller with onboard hub
- SATA II (3Gbps) disk drives in the 24 drive bays
- Hardware RAID6
- SAS 4x wide links (SFF-8470) to expansion enclosures
- S.M.A.R.T. and NCQ support
- Expansion enclosures:
 - S16S-J1000-R and S16S-J1000-S
- Maximum expansion: 88 drives (1 single-controller RAID + 4 JBOD)
- Intelligent load-balancing between host links by the EonPath™ multi-path software
- Embedded, browser-based RAIDWatch management tool
- Windows Logo Certificated

OVERVIEW

The Fibre-to-SATA RAID subsystem provides 4Gbps Fibre Channel interface for high-speed data transfer. It is fully compatible with cost-effective SATA II hard drives to offer tremendous storage capacity. The storage capacity can be further expanded by connecting the SAS 4x wide port to expansion enclosures which can house enterprise-class SAS drives or SATA hard drives.

The subsystem is equipped with redundant and hot-swappable components to ensure continuous and reliable operation. Advanced monitoring mechanisms are interfaced through firmware utility, RAIDWatch management software, and status LEDs etc. to ensure data security and subsystem protection.

APPLICATIONS

Infotrend products are widely applied in disk-to-disk backup, server-attached and network data storage and in major industries such as data-mining, medical imaging, security/CCTV, and digital media including video-on-demand, stream editing and more.

High Availability

- * Hot-swappable enclosure modules
- * Component redundancy
- * Intelligent reactive & preventive mechanisms
 - Automated cache flush
 - Automated Media Scan
 - Auto rebuild on hot spares
 - Automated caching mode switch
- * RAID controller transparent failover & failback capability

Advanced RAID Features

- * RAID levels 0, 1 (0+1), 3, 5, 6, 10, 30, 50, 60
- * RAID Parity regeneration
- * 64-bit LBA support
- * 3 spare disk types: dedicated, Global, enclosure-specific
- * Instant array availability
- * Stripe size and caching mode configurable per logical drive
- * Online array expansion by adding drives or copying & replacing drives
- * Online disk cloning

Management

- * Browser-based RAIDWatch manager
- * Java-based RAIDWatch manager
- * LCD keypad panel
- * Terminal console via RS-232 port
- * Telnet

Monitoring

- * S.M.A.R.T. status pooling
- * Voltage, module presence, temperature monitoring
- * Automated FRU status pooling

Operation Robustness

- * Intelligent read algorithms
- * Write cache threshold purge
- * Bad sector reassignment
- * Configurable task priority
- * Multiple, co-existing RAID arrays w/stripe sizes ranging from 16K to 1MB
- * Power-saving Drive Spin-down options
- * RAID level migration
- * RAID configuration on drives (drive roaming)

JBOD Characteristics

- * Single controller (S16S-J1000-S)
Redundant controller (S16S-J1000-R)
- * 2 SAS 4x wide ports per controller (SFF-8470)
- * Separate SAS domains to dual-ported SAS drives
- * Fault-tolerant hardware
- * Diagnostic LED panel
- * MUX kit for access from dual-controller RAID



AVAILABLE MODELS

Model	Controller	Host Port	Host Channel	Drive Bay	Expansion Port	JBOD Expansion
A24F-R2430	Redundant	8	4	24	2	1 RAID + 2 JBOD (56 HDD)
A24F-G2430	Single	4	2	24	1	1 RAID + 4 JBOD (88 HDD)



A24F-R2430



A24F-G2430

A24F-R/G2430 (RAID Subsystem)

CHARACTERISTICS

- RISC CPU
- Default DDR cache memory (per controller) 512MB
- 4G FC host channels (per controller) 2
- SAS 4x wide link expansion (per controller) 1
- BBU (per controller, optional on G model) 1
- COM ports (per controller) 2
- 10/100 Ethernet port (per controller) 1
- LCD keypad panel 1
- PSUs 3
- Cooling module 2
- Diagnostic LEDs on all FRUs

DRIVE INTERFACE

- SATA II (3Gbps)
- Number of disk trays 24

HOST CONNECTION PORTS

- SFP ports per controller 4
- Data single channel bandwidth 4Gbps
- Tag command queuing 256

RAID CONFIGURATIONS

- RAID levels 0, 1(0+1), 3, 5, 6, 10, 30, 50, 60
- Up to 32 logical drives (varies by memory size)
- Up to 1024 LUNs (varies by memory size)
- Up to 2GB cache per controller

HIGH AVAILABILITY

- Redundant, hot-swappable FRUs
- Subsystem self-diagnostics
- Li-Ion battery backup unit
- UPS status detection
- Multiple Local, Global, and enclosure-specific hot-spares

MANAGEMENT SOFTWARE

- Browser-based and Java-based RAIDWatch software
- Terminal via RS-232C
- Telnet over Ethernet
- Event notification methods:
E-mail/ Fax/ LAN broadcast/ SNMP traps/ SMS/ MSN

APPROVALS

- RoHS
- China RoHS
- Microsoft WHQL-Windows Server 2003

EMC

- CE
 - EN 55022: 1998/A1: 2000/A2: 2003
 - EN 61000-3-2: 2000/A1: 2001
 - EN 61000-3-3: 1995/A1: 2001
 - EN 55024: 1998/A1: 2001/A2: 2003
- FCC (FCC Part 15, subpart B)
- BSMI (CNS 13438)
- Safety
 - UL (60950-1: 2003)
 - BSMI
 - CNS 14336: 1993
 - IEC 60950-1, First Edition

OS SUPPORT

- Microsoft Windows 2000 Server
- Microsoft Windows 2003 Server
- Sun Solaris ver. 9/10
- RedHat Linux ver. 8/9, 64-bit, Enterprise ver.3
- SuSE: Linux ver. 8/9, 64-bit
- Fedora 64-bit
- Mac OS X version 10.4

REQUIREMENTS

- AC Input: 100VAC@16A ~ 240VAC@8A
405W with PFC
- DC Output:
+5 V/36A, +12 V/24A, +3.3 V/20A

Relative Humidity: 5% to 95% non-condensing

- Operating Temperature:
0°C to 40°C (without BBU)
0°C to 35°C (with BBU)

DIMENSIONS

- 4U, 19-inch rackmount chassis
- Without handles:
445(W) x 174.4(H) x 498(D) mm
(17.5 x 6.86 x 19.6 inches)
- With handles:
482(W) x 174.4(H) x 514(D) mm
(19 x 6.86 x 20.2 inches)

S16S-J1000-R/S (JBOD)

JBOD Characteristics

- SAS 4x wide port per controller 2
- PSUs 2
- Cooling module 2

Drive Interface

- SATA II
- Number of disk trays 16

Maximum Connection

- To dual-controller RAID 2
- To single-controller RAID 4

Requirements

- AC Input:
100VAC@9A ~ 240VAC@4.5A 530W with PFC
- DC Output:
12V-32A; 5V-32A; 3.3V-30A
- Relative Humidity:
5% to 95% non-condensing
- Operating Temperature:
0°C to 40°C

Asia Pacific
International Headquarters
Infortrend Technology, Inc.
8F, No. 102 Chung-Shan Rd., Sec. 3
Chung-Ho City, Taipei Hsien, Taiwan
Tel: +886-2-2226-0126
Fax: +886-2-2226-0020
sales.ap@infortrend.com
support.ap@infortrend.com
http://esupport.infortrend.com.tw
http://www.infortrend.com

Americas
Infortrend Corporation
2200 Zanker Road, Unit D,
San Jose, CA. 95131, USA
Tel: +1-408-988-5088
Fax: +1-408-988-6288
sales.us@infortrend.com
http://esupport.infortrend.com
http://www.infortrend.com/americas

Europe
Infortrend Europe Limited
1 Cherrywood, Stag Oak Lane
Chineham Business Park
Basingstoke, Hampshire
RG24 8WF, UK
Tel: +44-1256-707-700
Fax: +44-1256-707-889
sales.eu@infortrend.com
support.eu@infortrend.com
http://esupport.infortrend-europe.com
http://www.infortrend.com/europe

China
Infortrend Technology, Limited
Room 1210, West Wing, Tower One,
Junefield Plaza, No. 6 Xuanwumen Street,
Xuanwu District, Beijing, China.
Post code: 100052
Tel: +86-10-63106168
Fax: +86-10-63106188
sales.cn@infortrend.com
support.cn@infortrend.com
http://esupport.infortrend.com.cn
http://www.infortrend.com/china

Japan
Infortrend Japan, Inc.
6F, Okayasu Bldg.,
1-7-14 Shibaura Minato-ku,
Tokyo, 105-0023 Japan
Tel: +81-3-5730-6551
Fax: +81-3-5730-6552
sales.jp@infortrend.com
support.jp@infortrend.com
http://esupport.infortrend.com.jp
http://www.infortrend.com/japan